

# 台阶平行销

— p6-h7型 · p6-g6型/通孔螺纹型 —

Order 订货示例 型式 (1Type · 2D) — 3No. RD-KAPY3 — 10

型式	D公差		3No.	L	ℓ	ℓ1
1Type	2D	p6				
3	RD-KAPY (不锈钢)	+0.012	0	803	3	1
				8	4	
				805	5	
				1003	3	
				1005	5	
				10	7	
				12	6	
				15	10	
				20	13	
				(803)	3	
4	RD-KAPY (不锈钢)	+0.020	0	8	4	1.5
				805	5	
				1005	5	
				10	7	
				1008	8	
				1205	5	
				12	6	
				1208	8	
				(1508)	8	
				15	10	
5	RD-KAPY (不锈钢)	+0.020	0	1003	3	1.5
				1005	5	
				10	7	
				(1205)	5	
				12	6	
				1208	8	
				(1508)	8	
				15	10	
				1512	12	
				20	13	
6	RD-KAPY (不锈钢)	+0.020	0	1005	5	1.5
				10	7	
				1008	8	
				1205	5	
				12	6	
				(1208)	8	
				1508	8	
				15	10	
				1512	12	
				18	12	
8	RD-KAPY (不锈钢)	+0.024	0	20	13	2
				25	16	
				30	19	
				18	12	
				20	13	
				25	16	
				30	19	
				18	12	
				20	13	
				25	16	
10	RD-KAPY (不锈钢)	+0.015	-0.015	18	12	2
				25	16	
				30	19	
				18	12	
				20	13	
				25	16	
				30	19	
				18	12	
				20	13	
				25	16	
12	RD-KAPY (不锈钢)	+0.028	0	40	25	2
				40	25	

( ) 内尺寸仅适用 RD-KAPY

型式	D公差		3No.	L	ℓ	ℓ1	ℓ2	M×P
1Type	2D	p6						
6	RD-KAPYT (不锈钢)	+0.020	0	1205	5	1.5	8	4×0.7
				12	6			
				1208	8			
				1508	8			
				15	10			
				1512	12			
				18	12			
				20	13			
				20	13			
				20	13			
8	RD-KAPYT (不锈钢)	+0.024	0	20	13	2	10	5×0.8
				25	16			
				30	19			
				18	12			
				20	13			
				25	16			
				30	19			
				18	12			
				20	13			
				25	16			
10	RD-KAPYT (不锈钢)	+0.015	-0.015	25	16	2	10	6×1.0
				30	19			
				18	12			
				20	13			
				25	16			
				30	19			
				18	12			
				20	13			
				25	16			
				30	19			
12	RD-KAPYT (不锈钢)	+0.028	0	40	25	2	10	6×1.0
				40	25			

RD-KAPYT G型的公差p6侧端部形状与RD-KAPYGC相同。

Type	材质	硬度
RD-KAPYT	SUJ2	58HRC~
RD-KAPYTC	SUS440C	58HRC~

① ℓ1 · ℓ2尺寸可能会因外径研磨加工而大于产品目录中的值。

# 台阶定位销/绝缘定位销/树脂定位销

Order 订货示例 型式 (1Type · 2D) — 3L RD-KAPFW10 — 35

型式	D公差		3L	M×P	ℓ	d	dL
1Type	2D	p6					
3	RD-KAPFW (不锈钢)	+0.012	-0.002	803	3	1	5
				8	4		
				805	5		
				1003	3		
				1005	5		
				10	7		
				12	6		
				15	10		
				20	13		
				(803)	3		
4	RD-KAPFW (不锈钢)	+0.020	-0.004	8	4	1.5	5
				805	5		
				1005	5		
				10	7		
				1008	8		
				1205	5		
				12	6		
				1208	8		
				(1508)	8		
				15	10		
5	RD-KAPFW (不锈钢)	+0.020	-0.004	1003	3	1.5	5
				1005	5		
				10	7		
				(1205)	5		
				12	6		
				1208	8		
				(1508)	8		
				15	10		
				1512	12		
				20	13		
6	RD-KAPFW (不锈钢)	+0.020	-0.004	1005	5	1.5	5
				10	7		
				1008	8		
				1205	5		
				12	6		
				(1208)	8		
				1508	8		
				15	10		
				1512	12		
				18	12		
8	RD-KAPFW (不锈钢)	+0.024	-0.005	20	13	2	5
				25	16		
				30	19		
				18	12		
				20	13		
				25	16		
				30	19		
				18	12		
				20	13		
				25	16		
10	RD-KAPFW (不锈钢)	+0.015	-0.014	18	12	2	5
				25	16		
				30	19		
				18	12		
				20	13		
				25	16		
				30	19		
				18	12		
				20	13		
				25	16		
12	RD-KAPFW (不锈钢)	+0.028	-0.017	40	25	2	5
				40	25		

Type	材质	硬度
RD-KAPFW	SUJ2	58HRC~
RD-KAPFWM	SUS440C	58HRC~

型式	2D	3L	M×P	ℓ	d	dL
RD-KAPFW (不锈钢)	5	15	—	—	4	5
		25	—	—	—	10
	6	20	—	—	5	10
		30	3×0.5	6	5	15
	8	25	—	—	6	10
		35	4×0.7	8	6	15
	10	35	—	—	8	15
		40	5×0.8	8	8	15
	13	45	—	—	10	20
		55	6×1.0	10	10	25
70		—	—	—	30	

Order 订货示例 型式 (1Type · 2D) — 3L RD-KAPIP — 30

① 主体: 布类胶木 金属芯: SUS304  
② D尺寸公差为室温(20℃)下的测量结果。

型式	D公差		d	3L									
1Type	2D	0		8	10	15	20	25	30	35	40	45	50
RD-KAPIP	6	+0.03	3	8	10	15	20	25	30	35	40	45	50
				10	15	20	25	30	35	40	45	50	
	9	0	4	15	20	25	30	35	40	45	50		
				20	25	30	35	40	45	50			
12		5	20	25	30	35	40	45	50				
			25	30	35	40	45	50					

交货期 报价确定

小零件

小零件